



# GLASTER GLASTER D

## BUILDING PRODUCTS

### Technical Data Sheet

Revised: 09/28/2015

#### DESCRIPTION

Super lightweight filler with important thermal insulating properties. Particularly suitable for humid areas.

- + Solvent FREE
- + NOT crack
- + NOT retires
- + NOT require sanding
- + READY TO USE
- + EXTRA WHITE
- + HIGH YIELD

Suitable for:

- filling holes, cracks, fissures, missing parts on: wall, wood and ceramics. Thickness of 1 mm. up to and over 5 cm.
- renewing walls from rising humidity and heat insulating effects.
- paintable with any type of paint or water varnish.
- great to plaster frames and rosettes of polystyrene and polyurethane.
- filling joints in plasterboard

#### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils.

#### PRODUCT PREPARATION

One component ready to use acrylic filler.

#### APPLICATION

Apply GLASTER with a semi flexible grouting spatula.

#### CONSUMPTION

Determined by the thicknesses of filling

#### CLEANING

Clean the equipment with fresh water from that, otherwise remove mechanically.

#### CONTRAINDICATIONS

- + Do not use at temperatures below + 3 °C
- + Application is recommended between +10 °C and + 35 °C

#### PACKAGES

Bucket 250 ml. (box of 12/24 pcs.)	code 30118
Bucket 500 ml. (box of 12/24 pcs.)	code 30119/30124
Bucket 4 l. (boxes of 4 pcs.)	code 30120/30125
Bucket 8 l.	code 30121/30126
Bucket of 14 l.	code 30122/30127

#### STORAGE

The product is guaranteed for 12 months from the date of production. Avoid freezing.

#### TECHNICAL DATA

base:	acrylic
appearance:	thick paste of extra white color
solid:	about 85%
customs code:	3506 91 000 0
application temperature:	+ 10°C + 35°C
waiting time:	none
open time:	30 - 40 minutes
drying time:	48/72 hours

#### FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com