



PLASTER

BUILDING PRODUCTS

Technical Data Sheet

Revised: 09/28/2015

DESCRIPTION

Acrylic waterproofing sheath suitable to the protection of baths, showers, terraces and balconies.

- + Exceptional effectiveness
- + High yield
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties
- + Walkable

Suitable for:

- Waterproofing tile fundings in bathrooms, showers and damp rooms.
- balcony and terrace Waterproofing.
- flat roof and damp floor Waterproofing.

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy. The support must have a humidity: for cement surfaces max. 2% - for surfaces anhydrite. 0.5%.

On rough roads, it recommends the use of self-leveling cement-based.

To make the product effective even at low temperatures use our VI-SOLYN ST100 as a percentage of 10% on the amount of smoothing. We recommend using our PRIMER PU in the case of rising damp or humid surfaces.

PRODUCT PREPARATION

Ready to use. It is recommended to dilute the first coat with 5% of water.

PRODUCT APPLICATION

Once diluted, spread the product with a roller or a brush. Wait the product to be dried (about 8 hours) and then proceed with the second coat.

CONSUMPTION

About 1000/1500 g/m² (in 2 coats)

CLEANING

Clean the equipment with clear water.

CONTRAINdicATIONS

Do not apply on non-absorbent substrates. In case of ceramic tiles we recommend to sand the surface to make it porous. Before the laying, spread a coat of PRIMER AC. Dilute it 1: 5 with water. DO NOT FREEZE.

PACKAGES

| | |
|------------------------------------|------------|
| Jar of 750 ml in box No. 24 pieces | code 30134 |
| Tin 5 l in box number 4 pieces | code 30135 |
| Tins of 8 l | code 30136 |
| Tins of 14 l | code 30137 |

STORAGE

The product is guaranteed for 12 months from the date of production.

TECHNICAL DATA

| | |
|--------------------------|-------------------------|
| base: | acrylic |
| appearance: | creamy paste |
| colors: | white, gray, green, red |
| pH: | 6,5 |
| viscosity: | 2,500 cps |
| c.o.v. | <0.05 g/m ³ |
| percentage of solid: | 70% |
| customs code: | 3506 91 000 0 |
| application temperature: | + 5°C + 40°C |
| waiting time: | 6/8 hours |
| non flammable | |

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com