



REXILGUM

FLOOR PRODUCTS

Technical Data Sheet

Revised: 09/28/2015

DESCRIPTION

Water-based acrylic glue, ideal for all types of PVC coverings, linoleum and rubber floors.

Apply the adhesive in a single coat with a roller or a notched trowel No. 2.

- + Excellent open time
- + Strong final grip
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties

Suitable for:

- homogeneous vinyl and PVC floorings
- PVC tiles
- PVC floor coverings for ceramic or marble tiles
- linoleum flooring with jute
- natural cork floorings with PVC backing
- purl rough and smooth rubber natural floorings

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy. The support must have a humidity: for cement surfaces max. 3% - for the areas in anhydrite. 0.5%.

On rough roads, it recommends the use of self-leveling cement-based. To make the product effective even at low temperatures use our VISOLYN ST100 as a percentage of 10% on the amount of smoothing.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER PU in case of rising damp or too humid.

COVERING PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer.

PREPARATION OF ADHESIVE

The product is ready for use.

APPLICATION

SPATULA - Apply the product directly on the surface with a notched trowel n °2. Then proceed with the coating.

CONSUMPTION

250-350 g/m²

CLEANING

Clean possible spills with a damp sponge.

CONTRAINDICATIONS

- + Do not use for outdoor applications (using Adhesiva 2P/G).
- + Do not use at temperatures below + 3 ° C
- + Do not use on damp or subject to rising damp
- + Treat non-absorbent surfaces to make them porous.

PACKAGES

bucket 6 Kg
bucket 13 Kg
bucket 20 Kg

code 20027
code 20028
code 20029

STORAGE

The product is guaranteed for 12 months from the date of production. Preserve from frost. (+ 5 ° C + 40 ° C)

TECHNICAL DATA

base:	acrylic
appearance:	cream beige
pH:	6.5
viscosity:	20,000 to 25,000 cps
percentage of solid:	70%
customs code:	3506 91 000 0
application temperature:	+ 5 ° C + 40 ° C
waiting time:	15 - 20 minutes
open time:	30-40 minutes
setting time:	24 hours
non flammable	

FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com