



VK-M24

FLOOR PRODUCTS

Technical Data Sheet

Revised: 09/28/2015

DESCRIPTION

Water-based acrylic adhesive, ideal product for all types of carpets, PVC coverings, linoleum and needle punch floorings.

Apply the adhesive in a single coat with a roller or a notched trowel No. 2.

- + Fast setting
- + Strong initial tack
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties

Suitable for:

- all types of carpets
- linoleum
- polyester or polystyrene coatings
- needle punch floorings and fibre bonded carpets with PU supports
- natural cork wall coverings and PVC-backed wall coverings
- thermal and absorbent coatings

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils.

Any cracks must be sealed with our 2-component epoxy adhesive EPOXY.

The concrete surface must have a level of moisture : for cement surfaces max. 3% - for the areas in anhydrite. 0.5%.

For rough surfaces, it recommends the use a self-levelling cement-based products. To make these more performance even at low temperatures add the self-levelling product with our VISOLYN ST100 as a percentage of 10% on the total quantity of product.

We always recommend the use our PRIMER AC for consolidation and cleaning.

We recommend using our PRIMER PU in case of rising damp or too humid areas.

COATING PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer.

PREPARATION OF ADHESIVE

The product is ready for use.

APPLICATION

ROLLER - Apply the product directly on the floor with a short wool roller for about 10/15 m². Proceed in the application of the material.

SPATULA - Apply undiluted with a notched trowel No. 2 directly on the floor. Then proceed to the preparation of materials.

CONSUMPTION

250 - 350 g/m²

CLEANING

Clean possible spills with a damp sponge.

CONTRAINDICATIONS

- + Do not use for outdoor applications (using Adhesiva 2P/G).
- + Do not use at temperatures below + 3 °C
- + Do not use on damp or subject to rising damp
- + Treat non-absorbent surfaces to make them porous.

PACKAGES

bucket 6 Kg	code 20033
bucket 13 Kg	code 20034
bucket 20 Kg	code 20035

STORAGE

The product is guaranteed for 12 months from the date of production. Preserve from frost. (+ 5 °C + 40 °C)

TECHNICAL DATA PRODUCT

base:	acrylic
appearance:	cream beige
pH:	7.5
viscosity:	25,000 to 35,000 cps
c.o.v.:	<0.05 g/m ³
percentage of solid:	70%
customs code:	3506 91 000 0
application temperature:	+ 5 °C + 40 °C
waiting time:	10 - 15 minutes
open time:	20-30 minutes
setting time:	24 hours
not flammable	

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com